

Specification of 200mm, Pedestrian traffic light (NBRX213-2)



Specification

<i>Model:NBRX200-R</i>		<i>Model:NBRX200-G</i>	
<i>items</i>	<i>Parameters</i>	<i>items</i>	<i>Parameters</i>
<i>Size</i>	<i>200mm</i>	<i>Size</i>	<i>200mm</i>
<i>Color</i>	<i>Red</i>	<i>Color</i>	<i>Green</i>
<i>Leds(pcs)</i>	<i>64</i>	<i>Leds(pcs)</i>	<i>57</i>
<i>Wevelength</i>	<i>625±5</i>	<i>Wevelength</i>	<i>505±2</i>
<i>Module shape</i>	<i>Round</i>	<i>Module shape</i>	<i>Round</i>
<i>Power consumption</i>	<i><6W</i>	<i>Power consumption</i>	<i><6W</i>
<i>Housing material</i>	<i>PC</i>	<i>Housing material</i>	<i>PC</i>
<i>Voltage(V)</i>	<i>12-24VDC,100-277V AC</i>	<i>Voltage(V)</i>	<i>12-24VDC,100-277V AC</i>
<i>Luminace(cd)</i>	<i>800cd</i>	<i>Luminace(cd)</i>	<i>800cd</i>
<i>Operatingtemperature</i>	<i>-30 to+60</i>	<i>Operatingtemperature</i>	<i>-30 to+60</i>
<i>Insulation resistance</i>	<i>≥2M</i>	<i>Insulation resistance</i>	<i>≥2M</i>

Total Harmonic distortion	<20%	Total Harmonic distortion	<20%
IP rate	IP65	IP rate	IP65

Benefits

1. Wide working voltage
2. Water-dust proof, IP65
3. Long lifespan, 100,000 hours
4. Energy saving, low power consumption
5. Can not be opened, by unauthorized persons
6. Easy installation, can be mounted by horizontally as well as vertically
7. In accordance with EN12368, CE&ROHS, ISO9001:2008 certification obtained

Packing Details

Packing

Gather to pack:								
Model	Housing Material	Dim. of Outer Carton (mm)	Qty/Ctn	G.W./Ctn	N.W./Ctn	Packing	20GP/ Carton	40GP/ Carton
NBRX212-2	PC	640*330*250	1	5.17kgs	4.42kgs	Carton	586	1200

1. Put the product into PP protection film



2. Put lights into the foam to fix



5. Finish packing



3. Put accessories and light into carton



4. Put into foam and user manual



Different view



www.nobleled.com

Details



www.nobleled.com









